

22" Full HD LED Monitor

VA2259-sh



The ViewSonic® VA2259-sh is a 22" (21.5" viewable) Full HD LED monitor with SuperClear® AH-IPS Panel technology, offering clearly sharp color representation and outstanding screen performance at wide viewing angles. It is modernized with a minimalistic, borderless design which provides exceptional viewing experience for home entertainment or office work. It also carries eye-care technology, including Flicker-Free and Blue Light Filter, helping to eliminate eye strain from viewing for extended periods of time. Furthermore, Viewsonic's exclusive ViewMode™ provides intuitive presets to deliver optimized screen performance in different applications, with an energy-saving Eco-mode that enables users to do documental processing or internet surfing while saving. Built in with HDMI and VGA inputs, promising more flexible and reliable connectivity. With a 3-year warranty, Energy Star and EPEAT Silver certification, the VA2259-sh definitely is a great long-term investment for home and office users.

Key Features:

SuperClear IPS panel technology

Frameless design

Versatile connectivity

Full HD 1080p resolution

Superior color rendering and intuitive settings

Designed for:

Business

Home

22" Full HD LED Monitor

VA2259-sh

Specifications

LCD PANEL	Type	22" W (21.5" Viewable) AH-IPS Type
	Display Area	476.064mm x 267.786mm
	Resolution	Full HD 1920 x 1080
	Brightness	250 cd/m ² (Typ)
	Contrast Ratio	1000:1 (Typ), 700:1 (Min)
	Dynamic Contrast Ratio	50,000,000:1
	Viewing Angles	178° / 178° (Typ)
	Response Time	GTG: 5ms (Typ)
	Backlight	1 WLED light bar
	Backlight Life	30,000 Hrs (Min)
	Panel Surface	Anti-Glare type, Hard-coating (3H)
INPUT SIGNAL	Frequency	Fh=54~85.5KHz ; Fv=48~76Hz
	Sync	Separate Sync, Composite Sync, Sync on Green
COMPATIBILITY	PC	1920 x 1080 (Non-Interlaced)
	Mac®	1920 x 1080
CONNECTOR	Digital	HDMI x 1
	Analog	VGA x 1
	Audio Out	3.5 mm jack x 1
	Audio In	3.5 mm jack x 1
POWER	Power	3-pin plug (CEE22) x 1
	Voltage	AC 100-240V (Universal); 50/60Hz
	Consumption	22W ; Optimize:18W ; Conserve: 14W
ERGONOMICS	Tilt	22° ~ -5°
WALL MOUNT	VESA	100mm x 100mm
OPERATING CONDITIONS	Temperature	32°F to 104°F (0°C to 40°C)
	Humidity	20% to 90% (no condensation)
OPERATING CONDITIONS	Temperature	32°F to 104°F (0°C to 40°C)
	Humidity	20% to 90% (no condensation)
DIMENSIONS	Physical with stand	499.7 x 375.1 x 200mm
WEIGHT	Net with stand	2.84kg
REGULATIONS	CE EMC, CB, RoHS Green BOM & RoHS DoC, REACH SVHC List & DoC, ErP, WEEE, US NRTL w/ CA, FCC-B w/ ICES003, Energy Star , EPEAT Silver, Mexico-CoC, Mexico Energy, BSMI, PSB, RCM, MEPS, CCC, CEL Level 1, CECF	
WARRANTY	*Warranty offered may differ from market to market	
PACKAGE CONTENTS	LCD Display / Power Cable / VGA Cable / Quick Start Guide *Actual content may differ from market to market	