

48 inch Full HD Enhanced Viewing Comfort USB Playback Hospitality Mode Commercial Display



CDE4803



The ViewSonic CDE4803 is a great value, high performance 48" Full HD LED commercial display for hotel, restaurant and hospitality environments. In addition to versatile connectivity options, including HDMI, VGA, and SPDIF, the display comes with a simple and convenient USB multimedia playback functionality. With 1920x1080 resolution, 350-nit brightness, wide viewing angles and dual 10W stereo speakers, the slim-bezel CDE4803 delivers vivid images and remarkable sound for superior multimedia performance. The HDMI CEC pass-through support provides one-touch-play, with additional features for multiple connected devices such as HD set-top-boxes, media players, and Blu-ray™ players. An RS232 port with IR pass-through provides automated control for hospitality installation. Creating a more comfortable viewing experience, the display is equipped with Flicker-Free and Blue Light Filter technologies. In addition, free-bundled vController software offers easy maintenance and intuitive interfaces for remote management via a PC server or laptop.

Integrated USB Multimedia Player

This display features an integrated media player with a convenient USB playback function. Now photos, music, and 1080p video can be quickly displayed on-screen directly from a USB drive – without the need for a PC.

Free Bundled vController Software

Included vController software provides a simple and intuitive interface for remote management, OSD-related settings, and scheduling on deployed displays through RS232.



Hospitality Mode

This display is great for multi-screen setups in hotels, restaurants, sports bars, or retail outlets that require automated control and customizable presets. With a USB-programmable hospitality setting, each display will have the same customized channel default, audio level, front-panel lockout, and auto power-up settings.



Enhanced Viewing Comfort

Flicker-Free technology and a Blue Light Filter help to eliminate eye strain from extended viewing periods.



Control Multiple Devices

RS232 IR pass-through offers local control for set-top boxes, and other RS232 connected devices, directly with the display's remote controller. HDMI CEC functionality offers local control of DVD players, sound systems, and other HDMI connected devices, directly with the display's remote controller.



Dual Integrated Speakers

Designed with dual integrated speakers, this display combines incredible screen performance with stereo sound for an immersive multimedia experience. An additional speaker can be added via the SPDIF audio-out port for expanding sound to different locations in the room or venue, via cable.



Eye-care Technology



Technical Specifications

LCD PANEL	Panel Size	48"
	Type / Tech	TFT LCD Module with WLED Backlight
	Display Area	1054.08 x 592.92 mm
	Aspect Ratio	16:9
	Resolution	1920x1080
	Colors	1.06 Billion Colors
	Brightness	350 nits
	Contrast Ratio	4000:1 (typ.)
	Response Time	8 ms
	Viewing Angles	H = 178, V = 178 (typ.)
	Backlight	LED Backlight
	Backlight Life	30,000 Hours (typ.)
	Orientation	Landscape / Portrait
INPUT	HDMI	x2
	RGB / VGA	x1
	Audio	x1
	RS232	x1
OUTPUT	Audio	x1
	SPIDF	x1
	IR Pass Through	x1
USB	Type A	x1
SPEAKERS		10W x 2
COMPATIBILITY	RGB PC/HDMI PC	Up to 1920x1080 @60Hz.
	HDMI	480i, 480p, 720p, up to 1080p
POWER	Voltage	100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz
	Consumption	"On": Max 149 W, 115 W(Default) "Off"(Suspend): ≤ 0.5 W
Wall Mount	VESA®	200x200mm / 400x400mm ; Screw: M6*8 mm
OPERATING CONDITIONS	Temperature	41°F to 104°F (5°C to 40°C)
	Humidity	20% ~ 80% (non-condensing)
DIMENSIONS	Physical w/ stand	1081.8 x 663.1 x 329.6 mm
WEIGHT	Net w/ stand	13.39kg

REGULATIONS

CE, CB, FCC, Energy Star 7.0, BSMI, PSB, RCM

What's in the box?

CDE4803 commercial display / Remote Control with batteries / User manual CD wizard / Quick Start Guide / Power Cables / VGA cable / RS232

*Actual content may differ from market to market