

42" full HD 1920x1080p resolution



CDE4200-L



The ViewSonic CDE4200-L is the ideal display solution for business, hotel, and hospitality environments. The 42-inch Full HD LED professional display features versatile input connectivity including 3x HDMI, VGA, Composite, and YPbPr. With a brightness of 350 nits, and a 4000:1 contrast ratio, this LED panel display delivers stunning brightness and contrast at a 8ms response time to ensure crisp pictures and smooth playback. Built-in 10W x 2 speakers and SPDIF digital audio output provide crystal-clear sound. In addition, the CDE4200-LED includes USB cloning for easy duplication in multi-screen environments. The CDE4200-L also features automated control using RS232, HDMI CEC control, and IR pass through for easy connection to HD set-top-boxes, media players, and Blu-ray players. A programmable hospitality menu allows for custom calibration of features such as channel defaults, audio levels, and power up—making the CDE4200-LED ideal for use as in-room hotel televisions.



CDE4200-L

Full HD 1080p for Superior Pixel Performance

ViewSonic's CDE4200-L display features Full HD 1920x1080 resolution to deliver superior pixel-by-pixel performance for a more realistic viewing experience. At this resolution you'll experience greater image clarity and detail—qualities that will bring high-definition TV programs, HD movies and other multimedia content to life.



HDMI CEC Opens a World of HDMI Possibilities

With HDMI CEC functionality, remote controller signals can be transmitted via HDMI cable to connected HDMI devices. This enables out-of-sight DVD players, sound systems, and other devices to be directly controlled with the display's remote controller for a wider range of viewing possibilities.



IR Pass-through for Multi-device Control

The CDE4200-L's RS232 control port features IR pass-through to provide automated control for hospitality and commercial display installations. IR pass-through offers local control for set-top boxes or other connected devices, directly with the display's remote controller.



Handy USB Multimedia Playback

With the handy PC-less USB playback feature, photos and music can be immediately played and shared by plugging a USB drive into the display.



CDE4200-L

Hospitality Mode for Automated Multi-screen Control

The CDE4200-L is great for multi-screen setups in hotels, restaurants, sports bars, or retail outlets that require automated control and customizable presets. With a USB-programmable hospitality setting, each television can have the same customized channel default, audio level, front-panel lockout, and auto power-up settings.



Versatile Input Selection for Flexible Connectivity

With the CDE4200-L's versatile selection of inputs, you can easily connect and use a variety of digital equipment for use in hotel rooms and public areas. This includes an HDMI port to connect to high-definition content sources, USB and VGA ports, as well as composite and component inputs.



Energy-saving 30,000-hour LED Backlight

Our displays utilize energy-saving LED backlights with lifespans of over 30,000 hours – that's more than a decade of durability. Together with the advantages of significantly lower power consumption, it provides a lower cost of ownership along with a higher ROI, making the CDE4200-L a great long-term investment.



Dual 10W Stereo Speakers and External Speaker Out

The CDE4200-L display has two integrated 10-watt stereo speakers with SRS TruSurround HD for crystal-clear stereo sound. Users can also add an additional speaker via the SPDIF audio-out port. This allows users to conveniently expand their sound systems to different locations in the room or venue, via cable.



CDE4200-L

Modern VESA-mountable Design with Glossy Bezel and Removable Glass Stand

Designed to be displayed in high-traffic areas of hotel rooms, lobbies, restaurants, and other hospitality venues, the CDE4200-L display adds a sleek touch to any setting. With a glossy bezel and removable glass stand, this premium-value display looks as good as it performs. Also VESA-compliant, it accommodates more flexible mounting options on display stands and walls.



Remote Control-out Function Keeps Digital Devices Out of Sight

The RC control output function allows users to easily control DVD players, internet TV receivers, set-top boxes, and other devices – even when they are hidden out of sight. RC control output allows for the use of individual remote controls to transmit signals via IR transmitter to the attached and hidden digital devices.



Technical Specifications

LCD	Type	42" color TFT active matrix, wide LCD with WLED Backlight
	Display Area	36.6" horizontal x 20.6" vertical; 65" diagonal
	Optimum Resolution	1920x1080, 600mm dot pitch
	Contrast Ratio	3000:1 (typ)
	Viewing Angles	170° horizontal, 170° vertical
	Response Time	6.5ms
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	350 cd/m2 (typ)
	Aspect Ratio	16:9
	Panel Surface	Anti-glare, hard coating (3H)
INPUT	Video Input	HDMI, component, VGA, CVBS (BNC)
	Video Output	VGA, component
	Audio	Internal 10-watt (x2)
	Digital	HDMI (x3), YPbPr, CVBS, SPDIF, USB
	Control Input/Output	RS-232

VIDEO SIGNAL



42" full HD 1920x1080p resolution



CDE4200-L

	Video	480i, 480p, 720p, 1080i, 1080p
AUDIO	Speakers	Internal 10-watt (x2)
CONNECTOR	Analog	15-pin mini D-sub (VGA), RCA Audio In, headphone out
	Digital	HDMI (x3), YPbPr, CVBS, SPDIF, USB
	Power	3-pin plug
POWER	Voltage	AC 100–240V (universal), 50–60Hz
	Consumption	59W (typ)
CONTROLS	Picture	Picture Mode, Brightness, Contrast, Color, Tint, Sharpness, Backlight, Screen Size, Auto Adjust, H. Position, V.Position, Clock, Phase, Color Temperature, Dynamic Contrast, Film Mode, Noise Reduction, MPEG Noise Reduction
	Sound	Sound Setting, Digital Audio Output, Equalizer Setting, SRS Setting
	Panel	Menu, VOL +/-, Down/Up, Input, Power
	Special	Lock Parent Control, V-Chip, Movie Rating, English Rating, French Rating, Block UnRated Show, Change Password, Keypad Lock, Source Lock, System Lock
	Set Up	Closed Caption, Menu Language, Clock, OSD Transparency, Time Zone, Auto Clock, Setup Time, Day of Week, Daylight Saving Time, Time Format, OSD Timer
	Advanced Options	Blue Back, No Signal Power Off, No Operation Power Off, All Reset, Audio Only, Display ID, Usage Monitor
OPERATING CONDITIONS	Humidity	20–80% (non-condensing)
	Temperature (landscape)	32–104°F (0–40°C)
DIMENSIONS (WxHxD)	Physical Without Stand	38.4 x 24.6 x 2.5 in. / 974.2 x 626.3 x 64.4 mm
	Physical With Stand	38.4 x 26.7 x 8.2 in. / 974.2 x 679.2 x 210 mm
WEIGHT	Gross	34.0 lb. / 15.4 kg
	Net Without Stand	26.2 lb. / 11.9 kg
	Net With Stand	27.8 lb. / 12.6 kg
Regulations		FCC, CE, UL, RoHS



42” full HD 1920x1080p resolution



CDE4200-L

Wall Mount	200mm x 200mm
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
PACKAGE CONTENTS	CDE4200-L display, power cable, remote control with batteries, swivel base, User Guide, Quick Start Guide

