

48" Full HD Commercial Display



CDE4802



Technical Specifications

Display	Panel Size	47.6"
	Type/Tech	TFT LCD Module with LED Backlight
	Display Area (mm)	1054.08 (H) x 592.92 (V) mm / (47.6 " diagonal)
	Aspect Ratio	16:9
	Native Resolution	1920 x 1080
	Colors	16.7M



48" Full HD Commercial Display

CDE4802

Brightness	350 nits (typ.)
Contrast Ratio	1200:1 Typ.
Response Time	8ms
Viewing Angles	H = 178, V = 178 typ.
Backlight Life	30,000 Hours Typ.
Surface Treatment	Hard coating (3H)
Orientation	Landscape

INPUT

HDMI	x1 HDMI (1.3) + MHL, x1 HDMI
RGB / VGA	x1
DVI	x1
Audio	x1 PC audio(3.5 mm), x1 Shared RCA audio (L+R)
CVBS	x1 (Share with component Y)
YPbPr	x1
RS232	x1

OUTPUT

Audio	x1 Earphone Out
SPDIF	x1
Remote Control Out	x1

USB

Type A	x1 (Support FAT32 & FAT16 / NTFS (read only)
--------	--

SPEAKERS

10W x 2

COMPATIBILITY

RGB PC/HDMI PC	Refer to timing table
CVBS	480i,576i
YPbPr	480i, 480p,720p, up to 1080p
HDMI	480i, 480p,720p, up to 1080p
DVI	Up to 1920x1080 @60Hz

CONTROLS

Physical- Top OSD	PICTURE: Picture Settings Picture Mode(Power Saving/Dynamic /Stander/Movie/User), Screen Size (Wide/Cinema/Zoom/Normal) PC Settings Color Temperature (Normal/Warm/Cool) Backlight (Medium/High/Low) Advanced Picture Settings(Dynamic Contrast-Low/Medium/high/off; Film Mode-on/off; Noise Reduction-Low/Medium/high/off; MPEG Noise
-------------------	--

06052015



48" Full HD Commercial Display



CDE4802

	Multimedia	Reduction- low/Medium/high/off. SOUND: Sound Setting(Standard/Soft/User/Dynamc),Analog Sound, Digital Sound, Digital Audio Output, Equalizer Setting. PARENTAL: Lock Parent Control, V-CHIP,Change Password, Keypad Lock, Source Lock, System Lock. SETUP: Closed Caption, Menu Language(English/French/Spanish /German/Portuguese), Clock, OSD Transparency, OSD Timer. OTHERS: Blue Back, No Signal Power Off, No Operation Power Off, User Moniro, Audio Only, TV ID, All Reset. PICTURE: JPEG, BMP, PNG VIDEO: MPEG1, MPEG4/H.264, RM/ RMVB (1280*720@30p, Max.10Mbps) , MOV. MJPEG (640*480@30p Max.10Mbps) , DivX., FLV, VC-1 Decoder, WMA AUDIO: WAV, MP3, M4A (AAC, PCM, MPEG1, AC3, COOKER, Vorbis)
POWER	Voltage Consumption	100-240VAC +/- 10% 50/60Hz Wide Range 76W (typ), 95W (max) < 0.5 W ("Off")
ERGONOMICS	Wall Mount (VESA®)	200 x 200
OPERATING CONDITIONS	Temperature (° C) Humidity	0°C to 40°C 20% ~ 80% @40°C non-condensing
DIMENSIONS (W x H x D)	Physical (inch / mm) Packaging (inch / mm)	42.6x26.6x10.1 / 1082.4x676.1x255.6 (w/ stand) 42.6x24.7x3.4 / 1082.4x627.7x84.9 (w/o stand) 46.9 x 30.0x 2.6 / 1190 x 760x 165 (w/o Stand)
WEIGHT	Net (lb / kg) Gross (lb / kg)	23.6 / 10.7 (w/o stand) 27.56 / 12.5 (with Stand) 35.05 / 15.9
REGULATIONS		FCC, CE, CB, cTUVus or UL (by request), RoHS Mexico-UL CoC, HDMI logo, Dolby Digital
PACKAGE CONTENTS		

06052015



48" Full HD Commercial Display



CDE4802

1. CDE4800-L display 2. Remote Control with batteries 3. User manual wizard CD 4. Quick Start Guide 5. Power cable 6. Screw driver 7. (Optional) Glass Stand

*Actual content may differ from market to market

06052015

