

46" Slim Bezel Full HD 1080p Intel® OPS Ready Display

Grand Format for All-in-One Digital Signage Applications.

CDP4635



ViewSonic's new CDP4635 Full HD Commercial display features a FHD 1920x1080 panel with 4000:1 contrast and Intel's Open Pluggable Specification (OPS) for applications requiring an integrated media player. Additional features include versatile inputs – HDMI, DVI, VGA, S video and composite, YPbPr and built in 10W x 2 speakers. The CDP4635 will support up to a 5x5 display video wall with internal clock and scheduler. RS232 daisy chain and RJ45 are provided for automated remote control.

- ❶ 1080p 9ms panel for vibrant video and crisp images.
- ❷ Intel® OPS media player compatible
- ❸ Display wall capability up to 5x5.
- ❹ RS-232 daisy-chain capable.
- ❺ VGA and DVI inputs/outputs for flexible connectivity and control
- ❻ Remote and panel control lock out.
- ❼ Remote control JR45 port with real time clock & on-off scheduler
- ❽ Applications:
 - Quick service restaurant menus
 - Transportation - Arrival / Departure
 - DOOH Advertising
 - Campus signage
 - Hotels and Sports Bars

46" Slim Bezel Full HD 1080p Intel® OPS Ready Display

CDP4635



Specifications


LCD	Type: 46" color TFT active matrix, wide LCD Display Area: 40" horizontal x 22.5" vertical; 46" diagonal Optimum Resolution: 1920x1080, 530mm dot pitch Contrast Ratio: 4000:1 (typ) Viewing Angles: 178° horizontal, 178° vertical Response Time: 8ms Light Source: Long life, 50,000 hrs. (typ) Brightness: 400 cd/m2 (typ) Aspect Ratio: 16:9 Panel Surface: Anti-glare, hard coating (3H)
INPUT	Video Input: HDMI, DVI, component, VGA, S-Video, composite Video Output: VGA, component, DVI Control Input/Output: RS-232/RJ45
AUDIO OUTPUT	Speaker: 2 x 10w
INPUT SIGNAL	TV/Video Comp: 480i, 480p, 720p, 1080i, 1080p
CONNECTOR	Analog: 9-pin mini D-sub (VGA) Digital: HDMI, DVI Power: 3-pin plug
POWER	Voltage: AC 100–240V (universal), 50–60Hz Consumption: 220W (typ)
CONTROLS	Panel: Power, Exit, +, –, Menu/Enter Picture: Picture mode, contrast, brightness, color temperature, temperature adjust, sharpness VGA Setting: Auto adjustment, clock, phase, sharpness, H. position, V. position OSD Setting: Languages, OSD H. position, OSD V. position, OSD timer Input: VGA, DVI, HDMI, YPbPr Audio: Volume, mute, audio source Special: Aspect ratio, over scan, power save, image retention, auto adjustment, monitor ID, reset Diagnostic: Thermal, back light, ambient, 5V detect, 12 detect
OPERATING CONDITIONS	Temperature (landscape): 41–104°F (5–40°C) Temperature (portrait): 41–95°F (5–35°C) Humidity: 20–80% (non-condensing)
DIMENSIONS (W x H x D)	Physical with stand (optional): 43" x 26.8" x 13" (1091.1mm x 681.7mm x 328.3mm) Physical without stand: 43" x 25.4" x 4.7" (1091.1mm x 645.7mm x 120.1mm)
WEIGHT	Net with stand (optional): 58.1 lb. (26.5 kg) Net without stand: 57.3 lb. (22.6 kg) Gross without stand: 68.3 lb. (31 kg)
WALL MOUNT	VESA 400mm x 400mm
REGULATIONS	FCC, ICES003, UL, cUL, CE, CB, C-Tick, BSM
RECYCLE/DISPOSAL	The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.
WARRANTY	Three-year limited warranty on parts, labor and backlight

Package Contents

LCD display, power cable, remote control with batteries, User Guide CD



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.



Connectivity

Speaker switch
 Speakers out R/L
 Audio In
 Audio Out (RCA)
 Video In/Out
 Component In (BNC)
 VGA In (D-Sub)
 HDMI In
 DVI-D In
 VGA Out (D-Sub)
 RJ-45
 RS232C (Out/In)
 Main Power
 AC In

Resolutions Supported

640 x 480 at 60 Hz to 75 Hz
 800 x 600 at 50 Hz, 60Hz to 75 Hz
 1024 x 768 at 50 Hz, 60Hz to 75 Hz
 1280 x 768 at 50 Hz
 1360 x 768 at 50 Hz
 1280 x 1024 at 60Hz
 1600 x 1200 at 60 Hz
1920 x 1080 at 60Hz (recommended resolution)
 NTSC, PAL, SECAM, 4.43 NTSC, PAL 60
 Component: 480i, 480p, 720p, 1080i, 1080p

Specifications and availability subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16500-00B-01/13]

Sales: (888) 881-8781 or SalesInfo@ViewSonic.com • More product information: www.ViewSonic.com