

High Brightness Networkable WXGA Projector

Advanced Connectivity for Large Classrooms and Boardrooms

PJD7533w



HDMI®
HIGH DEFINITION MULTIMEDIA INTERFACE

The ViewSonic® PJD7533w is a high brightness networkable WXGA DLP® projector that offers bright widescreen images and advanced connectivity for large university classrooms and corporate boardrooms. Equipped with Crestron® LAN controller, the PJD7533w makes it easy for IT admin to remotely control and manage multiple projectors from their workstations. Built with BrilliantColor™ technology, this projector produces vibrant colors, while 4000 ANSI lumens and 15000:1 contrast ratio deliver bright, razor-sharp images. In addition, the PJD7533w is packed with advanced features including wired and wireless LAN display, USB display, a mobile app for smart phones and tablets, DICOM mode, capability for PC-less presentations, HDMI that is 3D Blu-ray ready, 1.6x optical zoom lens, and integrated speaker. The PJD7533w is the perfect projector for university classrooms and corporate settings where a powerful widescreen projection is necessary.

High Brightness for Large Classrooms & Corporate Boardrooms

Packed with 4,000 lumens and a high contrast ratio of 15,000:1 (w/ DynamicEco™), the PJD7533w is guaranteed to shine bright – even in large lecture halls and meeting rooms.

Widescreen Brilliance

With a native 1280x800 (WXGA) resolution, the PJD7533w wide format projector offers a tremendous degree of flexibility and compatibility. Whether connecting a widescreen notebook in the conference room, or watching 720p / 1080p HD content in the classroom, a distortion-free image with matching aspect ratio is guaranteed.

Mobile App for Smart Phones & Tablets

With the optional WPD-100 wireless USB adapter, you can use ViewSonic's app on your Android™ or iOS devices as a remote control for the projector. In addition, you can send and project content such as MS Office documents, PDFs, videos, or images directly from your mobile device. The ViewSonic mobile app also offers live draw and live cam functions to create an interactive experience for your presentation.



Network Monitoring & Control

IT admin can monitor, schedule, and manage the projector remotely, as well as receive projector status alerts, with the integrated Crestron® e-Control™ system and RoomView Express™ management software. Because the PJD7533w is Crestron® and AMX® certified, IT admin can control and monitor multiple projectors for any size campus or enterprise.

Wireless & Wired LAN Display

With its advanced networking capability, the projector can project images via wireless, or wired, LAN. The LAN display offers a quad split screen for simultaneously projecting content from up to 4 PCs, with the ability to broadcast from up to 8 projectors. The WPD-100 wireless adapter is required for wireless display.

PC-less Presentation

Jump start your presentation without waiting for the PC to boot up. With a PC-less presentation feature, you can display MS Office documents, PDFs, videos or images directly from a USB flash drive.

High Brightness Networkable WXGA Projector

PJD7533w



Wide Optical Zoom Lens

Equipped with a 1.6x optical zoom lens, the PJD7533w provides mounting flexibility with a wider throw distance range. This zoom lens also enables the projector to project images up to 50% larger than a conventional projector equipped with a 1.1x lens.



Plug n' Play USB Display

Project your presentations using a quick and simple plug-and-play USB connection without running a bulky VGA cable. Plug n' Play also features automatic resolution detection for the best imaging experience.



3D Blu-ray Ready HDMI

HDMI delivers the highest picture and sound quality without degradation. Equipped with the latest HDMI, ViewSonic's PJD7533w projector can display 3D images directly from 3D Blu-ray® players—perfect for connecting to any HDMI-enabled devices such as PCs, laptops, tablets, and media players.

Projection Distance		Screen Size (16:10) Diagonal	
Feet	Meters	Inches	Meters
3.3 - 4.1	1.0 - 1.3	32	0.8
8.3 - 10.3	2.5 - 3.2	80	2.0
10.4 - 12.9	3.2 - 3.9	100	2.5
15.6 - 19.4	4.7 - 5.9	150	3.8
20.8 - 25.9	6.3 - 7.9	200	5.1
26.0 - 32.3	7.9 - 9.9	250	6.4
31.2 - 38.8	9.5 - 11.8	300	7.6

Optional Accessories

Replacement Lamp RLC-081
3D Active Shutter Glasses..... PGD-series

DICOM SIM Mode Support

With the DICOM (Digital Imaging and Communications in Medicine) SIM mode, ViewSonic's PJD7533w is able to simulate and display multiple screens of X-rays, sonograms, and nuclear magnetic resonance (NMR) images. Whether for medical or educational presentations, the PJD7533w delivers the most accurate and detailed images.



Specifications

DISPLAY	Type	0.65" Digital Micromirror Device (DLP™)
	Resolution	WXGA 1200x800 (native)
	Lens	1.6x Manual optical zoom / manual optical focus
	Keystone	Vertical digital keystone correction (+/- 40°)
	Size	30 - 300 in. / 0.7 - 7.6 m (diagonal)
	Throw Distance	3.9 - 32.8 ft. / 1.2 - 10.0 m
	Throw Ratio	1.47-1.83:1
	Lamp	330 watt
	Lamp Life	2500 / 3500 hours* (Normal / Eco-mode)
	Brightness	4000 Lumens
	Contrast Ratio	15,000:1 (w/ DynamicEco™)
	Aspect Ratio	16:10 (native)
	Color Depth	30 bits, 1.07B Color (10+10+10)
	Color Wheel	6-seg RGBCYW / 7200rpm
INPUT SIGNAL	Computer and Video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SECAM (B, D, G, K, K1, L), SD 480i and 576i, ED 480p and 576p, HD 720p, 1080i, 1080p
	Frequency	Fh: 31-100KHz, Fv: 24-120Hz
COMPATIBILITY	PC	VGA to 1600x1200 UXGA
	Mac®	Up to UXGA (may require MAC adaptor)
CONNECTOR	RGB Input	15-pin mini D-sub (x2)
	RGB Output	15-pin mini D-sub
	Digital Input	HDMI
	Component Input	15-pin mini D-sub (x2, shared with RGB)
	Composite Input	RCA jack
	S-Video Input	4-pin mini-DIN
	Audio Input	3.5mm mini jack (x2)
	Microphone Input	3.5mm mini jack (shared with Audio 2)
	Audio Output	3.5mm mini jack
	Control	RS-232 (DB-9)
	LAN	RJ45
	USB	Type A (card reader and wireless dongle) Type B (mouse control and service), Mini Type B (USB display), 3.5mm plug 12V/1A
AUDIO	DC 12V Trigger	
	Speaker	16-watt (x1)

POWER	Voltage	100-240VAC (Auto Switching), 50/60Hz (universal)
	Consumption	350W (typ) / <0.5W (stand-by mode)
CONTROLS	Basic	Power, keystone/arrow keys, left, menu/exit, right, source, enter
	OSD	Picture, Video/Audio, Setting, Option, Language, Information (See user guide for full OSD functionality)
OPERATING CONDITIONS	Temperature	32°F-104°F (0°C-40°C)
	Humidity	10%-90% (non-condensing)
	Altitude	0-6,000 ft (1,800m), operational up to 10,000 ft (3,048m)
NOISE LEVEL	Normal / Eco-mode	34dB / 32dB
DIMENSIONS (W x H x D)	Physical	13.2 x 5.1 x 10.4 in. / 335 x 128.3 x 265 mm
	Packaging	15.0 x 13.5 x 9.5 in. / 383 x 342 x 242 mm
WEIGHT	Net	6.7 lbs. / 3.0 kg
	Gross	11.2 lbs. / 5.1 kg
REGULATIONS		CB, UL/cUL, FCC-B, NOM, KC, REACH, ErP, SVHC
		UL-Argentina, PSB, C-tick, SASO, CE, GOST-R, CCC, RoHS, WEEE, UkrSEPRO

What's in the box?

PJD7533w projector, power cable, VGA cable, remote control with batteries, carrying case, Quick Start Guide, ViewSonic Wizard DVD (with User Guide).



*Lamp life may vary based on actual usage and other factors. Programs, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. DLP® and DLP logo are registered trademarks of Texas Instruments and BrilliantColor™ is a trademark of Texas Instruments. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16456-00B-12/12]