

ViewSonic Accessibility Conformance Report

EN 301 549 Edition

(Based on VPAT[®] Version 2.5Rev)

Name of Product / Version:

IFP55G1-2 / VS21666

IFP65G1-2 / VS21667

IFP75G1-2 / VS21668

IFP86G1-2 / VS21669

Report Date: Oct. 13, 2026

Product Description:

IFPG1-2 series is a ViewSonic 55"/65"/75"/86" 4K interactive display series without an embedded operating system (No OS). The product contains no operating system or bundled software applications; all device-level accessibility is provided through the built-in OSD firmware and hardware and does not rely on user-installed assistive technology. The primary function of the product is to display content from externally connected devices; content shown from a

"Voluntary Product Accessibility Template" and "VPAT" are registered service marks of the Information Technology Industry Council (ITI)

connected computer is the responsibility of that computer's own operating system and assistive technology and is outside the scope of this product. Such content is out of scope of this report.

Contact Information: EPREL@viewsoniceurope.com

Applicable Standards/Guidelines

This report covers the degree of conformance for the following accessibility standard/guidelines:

Standard/Guideline	Included In Report
Web Content Accessibility Guidelines 2.0	Level A (No) Level AA (No) Level AAA (No)
Web Content Accessibility Guidelines 2.1	Level A (No) Level AA (No) Level AAA (No)
EN 301 549 Accessibility requirements for ICT products and services - V3.1.1 (2019-11) AND EN 301 549 Accessibility requirements for ICT products and services - V3.2.1 (2021-03)	Yes

Terms

The terms used in the Conformance Level information are defined as follows:

- **Supports:** The functionality of the product has at least one method that meets the criterion without known defects or meets with equivalent facilitation.
- **Partially Supports:** Some functionality of the product does not meet the criterion.
- **Does Not Support:** The majority of product functionality does not meet the criterion.
- **Not Applicable:** The criterion is not relevant to the product.
- **Not Evaluated:** The product has not been evaluated against the criterion. This can only be used in WCAG Level AAA criteria.

WCAG 2.1 Report

Table 1: Conformance Criteria, Level A

Not Applicable. The IFPG1-2 series has no embedded operating system, web browser, web content or software applications (no Android, myViewBoard, Manager or AirSync); therefore, WCAG 2.1 (corresponding to EN 301 549 Clause 9) does not apply.

Table 2: Conformance Criteria, Level AA

Not Applicable. The IFPG1-2 series has no embedded operating system, web browser, web content or software applications (no Android, myViewBoard, Manager or AirSync); therefore, WCAG 2.1 (corresponding to EN 301 549 Clause 9) does not apply.

Note: When reporting on conformance with the WCAG 2.1 Success Criteria, they are scoped for full pages, complete processes, and accessibility-supported ways of using technology as documented in the [WCAG 2.1 Conformance Requirements](#).

EN 301 549 Report

Clause 4: [Functional Performance Statements](#) (FPS)

Criteria	Conformance Level	Remarks and Explanations
4.2.1 Usage without vision Where ICT provides visual modes of operation, the ICT provides at least one mode of operation that does not require vision. This is essential for users without vision and benefits many more users in different situations.	Partially Supports	The IFPG1-2 series is a No-OS (no embedded operating system) interactive display and does not include a screen reader or built-in speech output (TTS). Basic functions such as power, volume and input source can be operated without vision using tactilely discernible physical buttons and the remote control; detailed settings in the OSD menu require vision. The primary function of the product is to display content from externally connected devices; content shown from a connected computer is the responsibility of that computer's own operating system and assistive technology and is outside the scope of this product. Therefore, this criterion is partially supported.
4.2.2 Usage with limited vision Where ICT provides visual modes of operation, the ICT provides features that enable users to make better use of their limited vision. This is essential for users with limited vision and benefits many more users in different situations.	Partially Supports	The OSD provides a high-contrast colour scheme and adjustable (enlarged) OSD text sizes to improve readability for users with limited vision. As the product has no operating system, a full-screen magnifier cannot be provided; therefore, this criterion is partially supported.
4.2.3 Usage without perception of colour Where ICT provides visual modes of operation, the ICT provides a visual mode of operation that does not require user perception of	Supports	The OSD interface and the LED indicator do not use colour as the only means of conveying information, indicating status or prompting an action. Non-colour cues such as text, icons,

Criteria	Conformance Level	Remarks and Explanations
colour. This is essential for users with limited colour perception and benefits many more users in different situations.		shapes or on/off and blinking patterns are also provided.
4.2.4 Usage without hearing Where ICT provides auditory modes of operation, the ICT provides at least one mode of operation that does not require hearing. This is essential for users without hearing and benefits many more users in different situations.	Supports	Core operation of the product does not rely on sound. Any audible prompt (e.g., mute or no-signal tone) has an equivalent visual indication on the OSD.
4.2.5 Usage with limited hearing Where ICT provides auditory modes of operation, the ICT provides enhanced audio features. This is essential for users with limited hearing and benefits many more users in different situations.	Supports	The product provides a sufficient volume adjustment range and a private listening output (3.5 mm audio jack) to meet the needs of users with limited hearing.
4.2.6 Usage with no or limited vocal capability Where ICT requires vocal input from users, the ICT provides at least one mode of operation that does not require them to generate vocal output. This is essential users with no or limited vocal capability and benefits many more users in different situations.	Supports	Vocal input is not required for the operation of the IFPG1-2 series.
4.2.7 Usage with limited manipulation or strength Where ICT requires manual actions, the ICT provides features that enable users to make use of the ICT through alternative actions not requiring manipulation, simultaneous action or hand strength. This is essential for users with limited manipulation or strength and benefits many more users in different situations.	Partially Supports	The force required to operate the physical buttons and the remote control is less than 22.2 N, and operation does not require complex gestures or simultaneous multi-point actions. The remote control is provided as an alternative input method. As the product has no operating system, OS-level assistive input such as Switch Access or auto-click is not available; therefore, this criterion is partially supported.

Criteria	Conformance Level	Remarks and Explanations
4.2.8 Usage with limited reach Where ICT products are free-standing or installed, all the elements required for operation will need to be within reach of all users. This is essential for users with limited reach and benefits many more users in different situations.	Supports	A remote control is included, and an optional telescopic stylus and wall mount are available. This installation flexibility allows operable parts to be placed within the user's reach.
4.2.9 Minimize photosensitive seizure triggers Where ICT provides visual modes of operation, the ICT provides at least one mode of operation that minimizes the potential for triggering photosensitive seizures. This is essential for users with photosensitive seizure triggers.	Supports	The OSD interface and indicator lights do not flash more than three times per second and do not use high-frequency visual effects, reducing the risk of photosensitive seizures.
4.2.10 Usage with limited cognition, language or learning The ICT provides features and/or presentation that makes it simpler and easier to understand, operate and use. This is essential for users with limited cognition, language or learning, and benefits many more users in different situations.	Partially Supports	The OSD navigation logic is consistent, the wording is simple and the icons are clear. As the product has no operating system, OS-level cognitive aids such as Reading Mode, Live Caption or Action Blocks are not available; therefore, this criterion is partially supported.
4.2.11 Privacy Where ICT provides features for accessibility, the ICT maintains the privacy of users of these features at the same level as other users.	Supports	Use of the accessibility features does not require disclosure of personal data; users of accessibility features have the same level of privacy as other users. Audio can be routed to headphones (private listening) to protect privacy.

Clause 5: Generic Requirements

Criteria	Conformance Level	Remarks and Explanations
5.1 Closed functionality	Heading cell – no response required	Heading cell – no response required
5.1.2 General	Heading cell – no response required	Heading cell – no response required
5.1.2.1 Closed functionality	See 5.2 through 13	The product has closed functionality (no operating system; users cannot install assistive technology). See information in 5.2 through 13.
5.1.2.2 Assistive technology	See 5.1.3 through 5.1.6	The closed functionality is operable without requiring users to attach, connect or install assistive technology. See information in 5.1.3 through 5.1.6.
5.1.3 Non-visual access	Heading cell – no response required	Heading cell – no response required
5.1.3.1 Audio output of visual information Where visual information is needed to enable the use of those functions of ICT that are closed to assistive technologies for screen reading, ICT shall provide at least one mode of operation using non-visual access to enable the use of those functions.	Not Applicable	The IFPG1-2 series is a No-OS (no embedded operating system) display and does not provide speech output (TTS). The primary function of the product is to display content from externally connected devices; content shown from a connected computer is the responsibility of that computer's own operating system and assistive technology and is outside the scope of this product. Therefore, this criterion is not applicable. Basic operations (power, volume and input source switching) can be performed without vision using tactilely discernible physical buttons; see 4.2.1.
5.1.3.2 Auditory output delivery including speech Where auditory output is provided as non-visual access to closed functionality, the auditory output shall be delivered:	Not Applicable	The product does not provide speech output (TTS); therefore, this criterion is not applicable (see 5.1.3.1 for the rationale).

Criteria	Conformance Level	Remarks and Explanations
a) either directly by a mechanism included in or provided with the ICT; or b) by a personal headset that can be connected through a 3,5 mm audio jack, or an industry standard connection, without requiring the use of vision.		
5.1.3.3 Auditory output correlation Where auditory output is provided as non-visual access to closed functionality, and where information is displayed on the screen, the ICT should provide auditory information that allows the user to correlate the audio with the information displayed on the screen.	Not Applicable	The product does not provide speech output (TTS); therefore, this criterion is not applicable (see 5.1.3.1 for the rationale).
5.1.3.4 Speech output user control Where speech output is provided as non-visual access to closed functionality, the speech output shall be capable of being interrupted and repeated when requested by the user, where permitted by security requirements.	Not Applicable	The product does not provide speech output (TTS); therefore, this criterion is not applicable (see 5.1.3.1 for the rationale).
5.1.3.5 Speech output automatic interruption Where speech output is provided as non-visual access to closed functionality, the ICT shall interrupt current speech output when a user action occurs and when new speech output begins.	Not Applicable	The product does not provide speech output (TTS); therefore, this criterion is not applicable (see 5.1.3.1 for the rationale).
5.1.3.6 Speech output for non-text content Where ICT presents non-text content, the alternative for non-text content shall be presented to users via speech output unless the non-text content is pure decoration or is used only for visual formatting. The speech output for non-text content shall follow the guidance for "text alternative" described in WCAG 2.1 [5] Success Criterion 1.1.1.	Not Applicable	The product does not provide speech output (TTS); therefore, this criterion is not applicable (see 5.1.3.1 for the rationale). All OSD icons are accompanied by visible text labels.

Criteria	Conformance Level	Remarks and Explanations
5.1.3.7 Speech output for video information Where pre-recorded video content is needed to enable the use of closed functions of ICT and where speech output is provided as non-visual access to closed functionality, the speech output shall present equivalent information for the pre-recorded video content.	Not Applicable	The closed functionality of the product does not require pre-recorded video for operation; therefore, this criterion is not applicable.
5.1.3.8 Masked entry Where auditory output is provided as non-visual access to closed functionality, and the characters displayed are masking characters, the auditory output shall not be a spoken version of the characters entered unless the auditory output is known to be delivered only to a mechanism for private listening, or the user explicitly chooses to allow non-private auditory output.	Not Applicable	The product has no operating system, and the OSD does not provide masked password or character entry; therefore, this criterion is not applicable.
5.1.3.9 Private access to personal data Where auditory output is provided as non-visual access to closed functionality, and the output contains data that is considered to be private according to the applicable privacy policy, the corresponding auditory output shall only be delivered through a mechanism for private listening that can be connected without requiring the use of vision, or through any other mechanism explicitly chosen by the user.	Not Applicable	The OSD only displays device settings and does not output personal or private data as speech; therefore, this criterion is not applicable.
5.1.3.10 Non-interfering audio output Where auditory output is provided as non-visual access to closed functionality, the ICT shall not automatically play, at the same time, any interfering audible output that lasts longer than three seconds.	Not Applicable	The product does not provide speech output (TTS); therefore, this criterion is not applicable (see 5.1.3.1 for the rationale).
5.1.3.11 Private listening volume	Not Applicable	The product does not provide speech output (TTS), so there is no private listening speech

Criteria	Conformance Level	Remarks and Explanations
Where auditory output is provided as non-visual access to closed functionality and is delivered through a mechanism for private listening, ICT shall provide at least one non-visual mode of operation for controlling the volume.		volume requirement; therefore, this criterion is not applicable. The volume of general audio from connected sources can be adjusted with the physical volume buttons.
5.1.3.12 Speaker volume Where auditory output is provided as non-visual access to closed functionality and is delivered through speakers on ICT, a non-visual incremental volume control shall be provided with output amplification up to a level of at least 65 dBA (-29 dBPaA).	Not Applicable	The product does not deliver speech output through its speakers; therefore, this criterion is not applicable. The volume of general audio from connected sources can be adjusted incrementally with the physical volume buttons.
5.1.3.13 Volume reset Where auditory output is provided as non-visual access to closed functionality, a function that resets the volume to be at a level of 65 dBA or less after every use, shall be provided, unless the ICT is dedicated to a single user.	Not Applicable	The product does not provide speech output (TTS), so there is no speech volume reset requirement; therefore, this criterion is not applicable.
5.1.3.14 Spoken languages Where speech output is provided as non-visual access to closed functionality, speech output shall be in the same human language as the displayed content provided, except: a) for proper names, technical terms, words of indeterminate language, and words or phrases that have become part of the vernacular of the immediately surrounding text; b) where the content is generated externally and not under the control of the ICT vendor, the present clause shall not be required to apply for languages not supported by the ICT's speech synthesizer; c) for displayed languages that cannot be selected using non-visual access;	Not Applicable	The product does not provide speech output (TTS); therefore, this criterion is not applicable (see 5.1.3.1 for the rationale). The OSD display languages cover the languages of the target markets (visual presentation).

Criteria	Conformance Level	Remarks and Explanations
d) where the user explicitly selects a speech language that is different from the language of the displayed content.		
5.1.3.15 Non-visual error identification Where speech output is provided as non-visual access to closed functionality and an input error is automatically detected, speech output shall identify and describe the item that is in error.	Not Applicable	The product does not provide speech output (TTS); therefore, this criterion is not applicable. When the OSD detects an input or setting error, the error is identified and described visually with a text message.
5.1.3.16 Receipts, tickets, and transactional outputs Where ICT is closed to visual access and provides receipts, tickets or other outputs as a result of a self-service transaction, speech output shall be provided which shall include all information necessary to complete or verify the transaction. In the case of ticketing machines, printed copies of itineraries and maps shall not be required to be audible.	Not Applicable	The product does not perform self-service transactions and does not produce tickets or receipts; therefore, this criterion is not applicable.
5.1.4 Functionality closed to text enlargement Where any functionality of ICT is closed to the text enlargement features of platform or assistive technology, the ICT shall provide a mode of operation where the text and images of text necessary for all functionality is displayed in such a way that a non-accented capital "H" subtends an angle of at least 0,7 degrees at a viewing distance specified by the supplier. The subtended angle, in degrees, may be calculated from: $\Psi = (180 \times H) / (\pi \times D)$ Where: • ψ is the subtended angle in degrees • H is the height of the text • D is the viewing distance	Supports	The OSD text is sized so that, at the specified viewing distance, the capital letter "H" subtends an angle of at least 0.7 degrees. A large OSD text size option is also available.

Criteria	Conformance Level	Remarks and Explanations
D and H are expressed in the same units		
5.1.5 Visual output for auditory information Where auditory information is needed to enable the use of closed functions of ICT, the ICT shall provide visual information that is equivalent to the auditory output.	Supports	Any auditory information needed for operation is also provided as an equivalent visual indication on the OSD.
5.1.6 Operation without keyboard interface	Heading cell – no response required	Heading cell – no response required
5.1.6.1 Closed functionality	See 5.1.3.1 through 5.1.3.16	The product does not provide speech output (TTS); criteria 5.1.3.1 through 5.1.3.16 are not applicable. See 5.1.3.1 for the rationale.
5.1.6.2 Input focus Where ICT functionality is closed to keyboards or keyboard interfaces and where input focus can be moved to a user interface element, it shall be possible to move the input focus away from that element using the same mechanism, in order to avoid trapping the input focus.	Supports	OSD navigation allows the input focus to be moved away from any element using the same mechanism (physical buttons or remote control), so the input focus is never trapped.
5.1.7 Access without speech Where speech is needed to operate closed functions of ICT, the ICT shall provide at least one mode of operation using an alternative input mechanism that does not require speech.	Supports	Speech is not required for the operation of the IFPG1-2 series.
5.2 Activation of accessibility features Where ICT has documented accessibility features, it shall be possible to activate those documented accessibility features that are required to meet a specific need without relying on a method that does not support that need.	Supports	Accessibility features such as high-contrast mode and OSD text size adjustment can be activated without relying on the ability they are intended to support. The activation options are presented in high contrast with sufficient text size and can be accessed via the remote control, the physical buttons or the OSD quick menu.

Criteria	Conformance Level	Remarks and Explanations
5.3 Biometrics Where ICT uses biological characteristics, it shall not rely on the use of a particular biological characteristic as the only means of user identification or for control of ICT.	Not Applicable	The product does not use biometrics for user identification or operation; therefore, this criterion is not applicable.
5.4 Preservation of accessibility information during conversion Where ICT converts information or communication it shall preserve all documented non-proprietary information that is provided for accessibility, to the extent that such information can be contained in or supported by the destination format.	Not Applicable	The product has no operating system and does not convert documents or data between formats; therefore, this criterion is not applicable.
5.5 Operable parts	Heading cell – no response required	Heading cell – no response required
5.5.1 Means of operation Where ICT has operable parts that require grasping, pinching, or twisting of the wrist to operate, an accessible alternative means of operation that does not require these actions shall be provided.	Supports	All operable parts (physical buttons and remote control) can be operated with one hand and do not require tight grasping, pinching or twisting of the wrist.
5.5.2 Operable parts discernibility Where ICT has operable parts, it shall provide a means to discern each operable part, without requiring vision and without performing the action associated with the operable part.	Partially Supports	The physical buttons on the front panel are in fixed positions with sufficient spacing, so they can be discerned by touch without activation. As OSD elements on the flat touch surface cannot be distinguished by touch, this criterion is partially supported.
5.6 Locking or toggle controls	Heading cell – no response required	Heading cell – no response required
5.6.1 Tactile or auditory status Where ICT has a locking or toggle control and the status of that control is visually presented to the user, the ICT shall provide at least one mode of operation where the status of the control can be	Does Not Support	The front panel provides two toggle buttons: Touch lock and Freeze screen. The status of these toggle controls is indicated visually on the screen only; no tactile or auditory indication of

Criteria	Conformance Level	Remarks and Explanations
determined either through touch or sound without operating the control.		their status is provided. Therefore, this criterion is not supported.
5.6.2 Visual status Where ICT has a locking or toggle control and the status of the control is non-visually presented to the user, the ICT shall provide at least one mode of operation where the status of the control can be visually determined when the control is presented.	Supports	The status of the Touch lock and Freeze screen toggle buttons can be determined visually through an on-screen indication when the controls are operated.
5.7 Key repeat Where ICT has a key repeat function that cannot be turned off: a) the delay before the key repeat shall be adjustable to at least 2 seconds; and b) the key repeat rate shall be adjustable down to one character per 2 seconds.	Not Applicable	The product has no key repeat function that cannot be turned off; therefore, this criterion is not applicable.
5.8 Double-strike key acceptance Where ICT has a keyboard or keypad, the delay after any keystroke, during which an additional key-press will not be accepted if it is identical to the previous keystroke, shall be adjustable up to at least 0,5 seconds.	Not Applicable	The product has no alphabetic or numeric keyboard or keypad; therefore, this criterion is not applicable.
5.9 Simultaneous user actions Where ICT has a mode of operation requiring simultaneous user actions for its operation, such ICT shall provide at least one mode of operation that does not require simultaneous user actions to operate the ICT.	Supports	The IFPG1-2 series does not require simultaneous user actions for its operation.

Clause 8: Hardware

Criteria	Conformance Level	Remarks and Explanations
8.1.1 Generic requirements	Heading cell – no response required	Heading cell – no response required
8.1.2 Standard connections Where an ICT provides user input or output device connection points, the ICT shall provide at least one input and/or output connection that conforms to an industry standard non-proprietary format, directly or through the use of commercially available adapters.	Supports	The IFPG1-2 series provides industry-standard, non-proprietary input/output connections, including HDMI, USB, USB-C, RS-232, RJ-45 and a 3.5 mm audio jack, to support compatibility with assistive technology and headphones.
8.1.3 Colour Where the ICT has hardware aspects that use colour, colour shall not be used as the only visual means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	Supports	The power LED conveys status through on/off and blinking patterns in conjunction with the on-screen display, so status is never identified by indicator colour alone.
8.2 Hardware products with speech output	Heading cell – no response required	Heading cell – no response required
8.2.1.1 Speech volume range Where ICT hardware has speech output, it shall provide a means to adjust the speech output volume level over a range of at least 18 dB.	Not Applicable	The product does not provide speech output (TTS); therefore, this criterion is not applicable. The volume of general audio from connected sources can be adjusted over a range of at least 18 dB via the physical buttons or the OSD.
8.2.1.2 Incremental volume control Where ICT hardware has speech output and its volume control is incremental, it shall provide at least one intermediate step of 12 dB gain above the lowest volume setting.	Not Applicable	The product does not provide speech output (TTS); therefore, this criterion is not applicable.
8.2.2.1 Fixed-line devices	Not Applicable	The product is not a fixed-line communication device intended to be

Criteria	Conformance Level	Remarks and Explanations
Where ICT hardware is a fixed-line communication device with speech output and which is normally held to the ear, it shall provide a means of magnetic coupling which meets the requirements of ETSI ES 200 381-1 [2] and shall carry the "T" symbol specified in ETSI ETS 300 381.		held to the ear; therefore, this criterion is not applicable.
8.2.2.2 Wireless communication devices Where ICT hardware is a wireless communication device with speech output which is normally held to the ear, it shall provide a means of magnetic coupling to hearing technologies which meets the requirements of ETSI ES 200 381-2.	Not Applicable	The product is not a wireless communication device intended to be held to the ear; therefore, this criterion is not applicable.
8.3 Stationary ICT	Heading cell – no response required	Heading cell – no response required
8.3.2.1 Unobstructed high forward reach Where no part of the stationary ICT obstructs the forward reach, at least one of each type of operable part shall be located no higher than 1220 mm (48 inches) above the floor of the access space. This is shown in Figure 2.	Supports	The IFPG1-2 series is a wall-mountable flat-panel interactive display; the installation height and position can be adjusted as needed. The product dimensions (W x H x D) are: IFP55G1-2: 1262.0 x 765.1 x 86.3 mm IFP65G1-2: 1483.9 x 891.2 x 87.4 mm IFP75G1-2: 1705.0 x 1015.7 x 87.6 mm IFP86G1-2: 1950.4 x 1153.7 x 87.6 mm Please refer to the installation guide. A remote control and an optional telescopic stylus are available so that operable parts can be within the reach height (≤ 1220 mm). Actual reachability depends on the installation.

Criteria	Conformance Level	Remarks and Explanations
8.3.2.2 Unobstructed low forward reach Where no part of the stationary ICT obstructs the forward reach, at least one of each type of operable part shall be located no lower than 380 mm (15 inches) above the floor of the access space. This is shown in Figure 2.	Supports	The installation height can be adjusted via wall mounting. Please refer to the installation guide so that operable parts meet the unobstructed low forward reach requirement (≥ 380 mm).
8.3.2.3.1 Clear space Where an obstruction is an integral part of the stationary ICT and hinders the access to any type of operable part, the ICT shall provide a clear space which extends beneath the obstructing element for a distance not less than the required reach depth over the obstruction.	Supports	The IFPG1-2 series is a flat-panel display with no integral obstruction. Please refer to the installation guide to meet the clear space requirement.
8.3.2.3.2 Obstructed (< 510 mm) forward reach Where the stationary ICT has an obstruction which is an integral part of the ICT and which is less than 510 mm (20 inches), the forward reach to at least one of each type of operable part shall be no higher than 1220 mm (48 inches) above the floor contact of the ICT. This is shown in Figure 3 (a).	Supports	The IFPG1-2 series is a flat-panel display with no integral obstruction and can be wall-mounted at an adjustable height to meet the requirement.
8.3.2.3.3 Obstructed (< 635 mm) forward reach Where the stationary ICT has an obstruction which is an integral part of the ICT and which is not less than 510 mm (20 inches) but is less than 635 mm (25 inches) maximum, the forward reach to at least one of each type of operable part shall be no higher than 1120 mm (44 inches) above the floor contact of the ICT. This is shown in Figure 3 (b).	Supports	The IFPG1-2 series is a flat-panel display with no integral obstruction and can be wall-mounted at an adjustable height to meet the requirement.
8.3.2.4 Knee and toe clearance width	Supports	The IFPG1-2 series is a flat-panel display with no operable parts that

Criteria	Conformance Level	Remarks and Explanations
Where the space under an obstacle that is an integral part of the stationary ICT is part of access space, the clearance shall be at least 760 mm (30 inches) wide.		obstruct the user's knees or toes, and can be wall-mounted at an adjustable height to meet the requirement.
8.3.2.5 Toe clearance Where an obstacle is an integral part of the stationary ICT, a space under the obstacle that is less than 230 mm (9 inches) above the floor is considered toe clearance and shall: a) extend 635 mm (25 inches) maximum under the whole obstacle; b) provide a space at least 430 mm (17 inches) deep and 230 mm (9 inches) above the floor under the obstacle; c) extend no more than 150 mm (6 inches) beyond any obstruction at 230 mm (9 inches) above the floor. This is shown in Figure 4.	Supports	The IFPG1-2 series is a flat-panel display with no operable parts that obstruct the user's toes, and can be wall-mounted at an adjustable height to meet the requirement.
8.3.2.6 Knee clearance Where an obstacle is an integral part of the stationary ICT, the space under the obstacle that is between 230 mm (9 inches) and 685 mm (25 inches) above the floor is considered knee clearance and shall: a) extend no more than 635 mm (25 inches) under the obstacle at a height of 230 mm (9 inches) above the floor; b) extend at least 280 mm (11 inches) under the obstacle at a height of 230 mm (9 inches) above the floor; c) extend at least 205 mm (8 inches) under the obstacle at a height of 685 mm (27 inches) above the floor; d) be permitted to be reduced in depth at a rate of 25 mm (1 inch) for each 150 mm (6 inches) in height.	Supports	The IFPG1-2 series is a flat-panel display with no operable parts that obstruct the user's knees, and can be wall-mounted at an adjustable height to meet the requirement.

Criteria	Conformance Level	Remarks and Explanations
This is shown in Figure 5.		
8.3.3.1 Unobstructed high side reach Where the side reach is unobstructed or obstructed by an element that is an integral part of the stationary ICT and which is less than 255 mm (10 inches), at least one of each type of operable part shall be within a high side reach which is less than or equal to 1220 mm (48 inches) above the floor of the access space. This is shown in Figure 6.	Supports	The product dimensions of the IFPG1-2 series (W x H x D) are: IFP55G1-2: 1262.0 x 765.1 x 86.3 mm IFP65G1-2: 1483.9 x 891.2 x 87.4 mm IFP75G1-2: 1705.0 x 1015.7 x 87.6 mm IFP86G1-2: 1950.4 x 1153.7 x 87.6 mm The installation height can be adjusted via wall mounting so that the unobstructed high side reach is ≤ 1220 mm. Please refer to the installation guide.
8.3.3.2 Unobstructed low side reach Where the side reach is unobstructed or obstructed by an element that is an integral part of the stationary ICT and which is less than 255 mm (10 inches), at least one of each type of operable part shall be within a low side reach which is greater than or equal to 380 mm (15 inches) above the floor of the access space. This is shown in Figure 6.	Supports	The installation height can be adjusted via wall mounting so that the unobstructed low side reach is ≥ 380 mm.
8.3.3.3.1 Obstructed (≤ 255 mm) side reach Where stationary ICT has an obstruction which is an integral part of the ICT, the height of the obstruction shall be less than 865 mm (34 inches). Where the depth of the obstruction is less than or equal to 255 mm (10 inches), the high side reach to at least one of each type of operable part shall be no higher than 1220 mm (48 inches) above the floor of the access space. This is shown in Figure 7 (a).	Supports	The IFPG1-2 series is a flat-panel display and can be wall-mounted at an adjustable height to meet the requirement.

Criteria	Conformance Level	Remarks and Explanations
8.3.3.3.2 Obstructed (≤ 610 mm) side reach Where stationary ICT has an obstruction which is an integral part of the ICT, the height of the obstruction shall be less than 865 mm (34 inches). Where the depth of the obstruction is greater than 255 mm (10 inches) with a maximum depth of 610 mm (24 inches), the high side reach to at least one of each type of operable part shall be no higher than 1 170 mm (46 inches) above the floor of the access space. This is shown in Figure 7 (b).	Supports	The IFPG1-2 series is a flat-panel display and can be wall-mounted at an adjustable height to meet the requirement.
8.3.4.1 Change in level Where stationary ICT has a floor within it, then any change of floor level within it or entering it shall be ramped with a slope no steeper than 1:48. Exceptions: a) If the change in floor level is less than or equal to 6,4 mm ($\frac{1}{4}$ inch) the change may be vertical as shown in Figure 8. b) If the change in floor level is less than or equal to 13 mm ($\frac{1}{2}$ inch) the change may have a slope not steeper than 1:2 as shown in Figure 9.	Not Applicable	The product does not have a floor as part of its structure; therefore, this criterion is not applicable.
8.3.4.2 Clear floor or ground space Where stationary ICT has an operating area within it, it shall provide a clear floor area that has the minimum dimensions of 760 mm (30 inches) by 1 220 mm (48 inches) from which to operate the ICT. This is shown in Figure 10.	Not Applicable	The product does not have an operating area with floor space; therefore, this criterion is not applicable.
8.3.4.3.2 Forward approach Where the operating area is inside an alcove within the stationary ICT, the alcove is deeper than 610 mm (24 inches), and where a	Not Applicable	The product does not have an operating area within an alcove; therefore, this criterion is not applicable.

Criteria	Conformance Level	Remarks and Explanations
forward approach is necessary, the dimension of the access space shall be a minimum of 915 mm (36 inches) wide. This is shown in Figure 11.		
8.3.4.3.3 Parallel approach Where the operating area is inside an alcove within the stationary ICT, the alcove is deeper than 380 mm (15 inches), and where a parallel approach is possible, the dimension of the access space shall be a minimum of 1 525 mm (60 inches) wide. This is shown in Figure 12.	Not Applicable	The product does not have an operating area within an alcove; therefore, this criterion is not applicable.
8.3.5 Visibility Where stationary ICT provides one or more display screens, at least one of each type of display screen shall be positioned such that the information on the screen is legible from a point located 1015 mm (40 inches) above the centre of the floor of the operating area).	Supports	The IFPG1-2 series can be wall-mounted at an adjustable height so that the display screen is legible from a point 1015 mm above the floor.
8.3.6 Installation instructions Installation instructions shall be made available for all stationary ICT. These instructions shall give guidance on how to install the ICT in a manner that takes into account applicable requirements for accessibility of the built environment as they apply to the installation of the ICT. Where there are no such requirements the instructions should require that the dimensions of the installed ICT conform to clauses 8.3.2 to 8.3.5 of the present document.	Supports	Please refer to the installation instructions provided by ViewSonic, which include guidance on installation dimensions and heights.
8.4 Mechanically Operable parts	Heading cell – no response required	Heading cell – no response required
8.4.1 Numeric keys	Not Applicable	The product has no physical numeric keys arranged in a rectangular keypad; therefore, this criterion is not applicable.

Criteria	Conformance Level	Remarks and Explanations
Where provided, physical numeric keys arranged in a rectangular keypad layout shall have the number five key tactilely distinct from the other keys of the keypad.		
8.4.2.1 Means of operation of mechanical parts Where a control requires grasping, pinching, or twisting of the wrist to operate it, an accessible alternative means of operation that does not require these actions shall be provided.	Supports	Mechanical operable parts do not require tight grasping, pinching or twisting of the wrist, and an alternative means of operation (remote control) is provided.
8.4.2.2 Force of operation of mechanical parts Where a control requires a force greater than 22,2 N to operate it, an accessible alternative means of operation that requires a force less than 22,2 N shall be provided.	Supports	The force required to activate operable parts is less than 22.2 N (5 lbs).
8.4.3 Keys, tickets and fare cards Where ICT provides keys, tickets or fare cards, and their orientation is important for further use, they shall have an orientation that is tactilely discernible.	Not Applicable	The product does not provide keys, tickets or fare cards; therefore, this criterion is not applicable.
8.5 Tactile indication of speech mode Where ICT is designed for shared use and speech output is available, a tactile indication of the means to initiate the speech mode of operation shall be provided.	Not Applicable	The product does not provide a speech mode (speech output); therefore, this criterion is not applicable. The physical buttons are tactilely discernible; see 5.5.2.

Clause [11: Software](#)

Not Applicable. The IFPG1-2 series has no operating system or bundled software applications. Requirements for the closed functionality of the OSD are covered in Clause 5; therefore, Clause 11 (Software) does not apply.

Clause 12: Documentation and Support Services

Criteria	Conformance Level	Remarks and Explanations
12.1 Product documentation	Heading cell – no response required	Heading cell – no response required
12.1.1 Accessibility and compatibility features Product documentation provided with the ICT whether provided separately or integrated within the ICT shall list and explain how to use the accessibility and compatibility features of the ICT.	Supports	The product documentation lists and explains the accessibility and compatibility features of the product, including high-contrast mode, OSD text size adjustment, operation via the physical buttons and remote control, and use of the private listening output (3.5 mm audio jack). ViewSonic provides product documents on the product website and the official Support & Service web page.
12.1.2 Accessible documentation Product documentation provided with the ICT shall be made available in at least one of the following electronic formats: a) a Web format that conforms to the requirements of clause 9; or b) a non-web format that conforms to the requirements of clause 10.	Supports	Product documentation is provided in an accessible electronic format that meets the requirements of Clause 10 (non-web documents) or Clause 9 (web content).
12.2 Support Services	Heading cell – no response required	Heading cell – no response required
12.2.2 Information on accessibility and compatibility features ICT support services shall provide information on the accessibility and compatibility features that are mentioned in the product documentation.	Supports	ViewSonic support services provide information on the accessibility and compatibility features described in the product documentation.
12.2.3 Effective communication	Supports	ViewSonic support services accommodate the communication

ICT support services shall accommodate the communication needs of individuals with disabilities either directly or through a referral point.		needs of users with disabilities, either directly or through a referral point.
12.2.4 Accessible documentation Documentation provided by support services shall be made available in at least one of the following electronic formats: a) a Web format that conforms to clause 9; or b) a non-web format that conforms to clause 10.	Supports	Documentation provided by ViewSonic support services is available in an accessible electronic format that meets the requirements of Clause 10 (non-web documents) or Clause 9 (web content).

Legal Disclaimer (Company)

This Conformance Report is provided by ViewSonic Corporation for informational purposes only. It outlines the product's accessibility features based on evaluations conducted as of the report's publication date. This document does not serve as a legally binding assurance of compliance with any accessibility laws or standards.

The report reflects internal assessments and product specifications available at the time of testing. Accessibility performance may vary depending on firmware versions, device configurations, operating environments, connected source devices, and assistive technologies used.

While ViewSonic strives to maintain accessibility across its products, the information provided here may become outdated due to future updates or changes. Customizations or modifications made by users, integrators, or third parties may affect accessibility and could render portions of this report inaccurate or no longer applicable.

This document is not intended to replace independent assessments by users or institutions. Customers are encouraged to conduct their own evaluations to determine whether the product meets their accessibility and compliance requirements.

ViewSonic is not responsible for the accessibility or accuracy of any third-party content or services that may be integrated into or used in conjunction with ViewSonic products. Responsibility for such content remains with the original provider, including the management of privacy or consent requirements.

Unless otherwise specified in a written agreement, ViewSonic products and related services are provided "as is." No warranties are expressed or implied, including but not limited to warranties of merchantability, fitness for a particular purpose, non-infringement, or uninterrupted operation.

To the extent allowed by law, ViewSonic will not be liable for any indirect, incidental, special, or consequential damages resulting from the use of or inability to use the product, including but not limited to loss of business, revenue, data, or productivity, even if previously advised of the possibility of such damages.